

Infrared Multi-Touch Screen

ETS E Series

Technical Specification

Customer Approved

采购部 PURCHING	品管部 QC	研发部 R&D	签章

Manufacturer

拟制 DRAWING	审核 1 CHECK1	审核 2 CHECK2	批准 RATIFY	签章

Version	Date	Information Source	Update Details
1.0	2015-1-26		Release



1 Characteristics


EverTouch E series infrared multi-touch screen is designed with thin and slim frame. It can be integrated into LCD monitor or any flat display device easily, and providing new look of display devices.

Features:

- True multi-touch points
- Support from 2 to 10 touch points
- Integrated controller
- Fast response and writing smoothly
- High precision
- Stable and no drift
- · Work well under direct sunlight

Typical Applications:

- All-in-one computer
- Video conference system
- Kiosks
- Self-service terminal
- Interactive advertising machine



2 Specifications

2.1 GENERAL SPECIFICATIONS

Item	Description	Remarks
Touch Input Method	Pen, Finger, Finger of gloved	
	hand Activation	
Detection Method	Infrared rays	
Available Touch Point	Max. 10 points simultaneous	
Response Time	First click<16ms	
	Repeated click<6ms	
Ambient Light	Operating normally with sunlight	As angle of incidence to
	below 100k lux	touch panel $$ 20 $^{\circ}$ $$ \sim
		90°
Available Object Size for	Multi-touch: Min. Ф6mm	
Touch	Single-touch: Min. Ф3mm	
Operation System	Windows 8/7/XP, MAC OS X,	
	Linux, Android	

2.2 MECHANICAL SPECIFICATIONS

Item	Description	Remarks
Frame	Black	
Touch Area	(H) x (V)	
Outside Size	(H) x (V)	
Thickness	8.2mm	
Surface durability	Vickers hardness 5.0~7.0GN/m²	




2.3 ELECTRICAL SPECIFICATIONS

Item	Description		Remarks
Operation Voltage	DC 4.75 to 5.25V		
Power Consumption	<1W		
Interface	USB 2.0 (full speed)		A type plug
	Serial port		115200bps
ESD	Contact 4KV		
	Air	8KV	

2.4 RELIABILITY

ITEM	Specification	Specification	
Ambient	Operating	-20℃~60℃	
Temperature	Storage	-40℃~85℃	
Humidity	10%~90%RH		
Warranty	1 year	1 year	

3 Mechanical Dimension



Remark: Standard length of USB cable is 800mm (Customization available)

Model	Length(Outside)	Width(Outside)	Length(Touch Area)	Width(Touch Area)
E-«SIZE»-X	«H»	«W»		

Dimensions (Ratio Unit: mm)



4 Ordering information

$$E - X1 - X2 - X3$$
(1) (2) (3) (4)

Notes (S2 series):

Part	Information	Value	Remark
name			
(1)	Product Series	Е	
(2)	Active Area of	15,17,19,21.5	Unit: inch
	Display		
(3)	Available Touch	2, 4, 6, 10.	
	point simultaneous		
(4)	Interface type	UA, UB, C	UA=USB A type plug
			UB= USB B type plug
			C= Other interface

Example:

E-9-2-UA: E series product with size of 19 inch, 2-point true touch points, USB A type.

5 RoHS Compliance

EverTouch S2 series are RoHS compliant.